













Model Part#
RC2315 8951077130

Model		RC2315
Anvil		3/4"
Working Torque		1100 Nm
Max Torque		1500 Nm
Speed		5600 min ⁻¹
Weight		4.7 kg
Hose		13 mm
Dimension axbxc		242x230x78 mm
Air cons.		340 l/min
Air cons.		990 l/min
Air inlet		3/8" IG
Impact system		DUOPACT
Sound LpA		91.1 dB(A)
Vibration		9.97 m/s ²

1500 Nm max.



- 3/4" square drive impact wrench
- DUOPACT mechanism
- 3 position regulator in forward
- Full power in reverse
- Insulating rubber sleeve on handle

Accessories for 3/4" impacts

Model Part#
RS618 8951012358



- 3/4" square drive
- 8 pieces
- (26, 27, 29, 30, 32, 35, 36, 38)

Model Part#
RC2377 8951000045 short anvil
RC2387 8951000074 long anvil

Model		RC2377 / RC2387
Anvil		3/4"
Working Torque		1300 Nm
Max Torque		1950 Nm
Speed		5760 min ⁻¹
Weight		3.5 / 4.1 kg
Hose		13 mm
Dimension axbxc		RC2377 225x84x199 mm RC2387 300x84x199 mm
Air cons.		255 l/min
Air cons.		972 l/min
Air inlet		3/8" IG
Impact system		DOUBLE DOG
Sound LpA		96.8 dB(A)
Vibration		14.5 m/s ²

1950 Nm max.



- 3/4" square drive impact wrench
- Injected TPR grip
- 3 positions in forward, full power in reverse
- Great teasing for optimal control
- 1950 Nm max torque
- Composite housing, only 3,38 kg even at this high power level
- Forged DUOPACT mechanism
- Impact mechanism housing made of steel and aluminium
- Swivel air inlet
- Mini grease plug on the front housing

RC2387
Anvil extension 75mm

