

# Planar LA1500R

## Open Frame Display

The Planar® LA1500R is a 15" open frame non-touch monitor. The Planar LA1500R delivers a cost-effective display solution for OEM's and integrators to easily integrate into kiosk enclosures.



SPECIFICATION	DETAIL
Product Name	LA1500R
Planar Part Number	997-5803-02
Brightness (Typical)	250 cd/m <sup>2</sup>
Contrast Ratio (typ)	600:1
Response Time (typ)	8 ms
Horizontal Scan	31.5 ~ 60 KHz
Viewing Angle (typ)	160° H,V
Pixel Pitch	0.297 mm
Refresh Rate	56 to 75 Hz
Video Inputs	Analog
Power Supply	External Module with IEC320 Connector, USA Cord-set, UL1950 certified
Power Requirements	100-240 VAC, 50/60Hz
Power Consumption (max)	21W (1W standby, 0.5 off)
External Connections	Video Input: D-sub, 15 pin; DC Power Input: 4 pin, mini DIN;
Options / Features	Anti-glare coating, Multi-language support, On screen display (OSD)
Viewable Size	304 mm x 228 mm (15" diagonal)
Display Resolution	1024 x 768 native. Supports IBM and Mac VGA; VESA VGA, SVGA.
Dimensions (W x H x D)	14.17" x 10.63" x 1.81" (360 mm x 270 mm x 46 mm)
Display Weight	7.9 lbs (3.6 kg) net; 13 lbs (5.9 kg) shipping
Product Approvals	UL, FCC-B, CE-B, TUV, RoHS
Operating Temperature	+5° to +35° C

<b>Recommended Usage</b>	Up to 16 hours per day
<b>Service and Support/Warranty</b>	3-Year Customer First™ Warranty featuring FREE 2-Day Advance Replacement (US only). Please see warranty document for more details and for replacement procedures outside the US.
<b>VESA Compatible/Location</b>	Adjustable rear panel mounting brackets included, VESA 75 mm compatible
<b>UPC</b>	8 10689 05803 8

For more information, please visit [www.planar.com](http://www.planar.com)

*Specifications are subject to change without notice.*

*Specification Report Date: 2/22/2018*

*© Copyright 2018 Planar Systems, Inc. All rights reserved*