

**PNOZ s30 C 24-240VACDC 2 n/o 2 n/c**

751330



PNOZsigma Safety relay (standalone). Outputs: 2 N/O, 2 N/C, UB 24 - 240 V AC/DC, width: 45 mm  
Speed-, standstill monitor, proximity switch and/or incremental encoder, display operation push & turn, plug-in spring-loaded terminals, expansion with PNOZsigma Contact expansion.

On request

**1**

PC

Available ex-stock

Availability

**Technical details**

Certifications:	CE, cULus Listed, EAC (Eurasian), TÜV, CCC
Application options:	Speed monitoring, Standstill monitoring
Operating modes:	Single-channel, Automatic reset, Dual-channel, Manual reset, Monitored manual reset
Standards:	EN 1088, EN 60204-1, EN 62061, EN ISO 10218-1, EN ISO 13849-1, VDI 2854
Supply voltage (V):	24,0 - 240,0
Supply voltage type:	AC/DC
Terminal type:	Spring-loaded terminal
Max. current at DC13 I (6 cycles/min):	4.0 A
Width dimension:	45.0 mm
Height dimension:	100.0 mm
Depth dimension:	120.0 mm
Gross weight:	420 g
Net weight:	400 g
Ambient temperature:	-20 - 55 °C

**Related Products**

Top

