

PILOT LAMPS (ex : CRP-25AR)

Model	Code			Content
CRP-	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pilot Lamp
Installing hole	25			Ø25
	30			Ø30
Power voltage	A			100 - 240 VAC
	D			12 - 24 VDC / AC
Actuator color (cap color)	R			R (Red), G (Green), Y (Yellow), A (Blue), W (White), B(Black)

Model	PILOT LAMPS	
	Flush Ø30	Flush Ø25
Appearance		
Actuator code	CRP-30	CRP-25

Contact configuration	1a1b	
Operation of contact	Slow-action	
Installing panel thickness	1 ~ 6 mm (without the additional accessories)	
Rated voltage / Current consumption	100 - 240 V a.c. / Max. 4.4 VA	
	380 V a.c. / Max. 2.7 VA	
	12-24 V d.c. / Max. 18 mA	
Allowable operating frequency	Mechanical	Max. 30 operations/min
	Electrical	Max. 30 operations/min
Insulation resistance	Min.100 MΩ	
Dielectric strength	1500 V a.c. 50/60 Hz for 1 min	
Vibration	Malfunction Resistance	10 - 55 Hz double amplitude width 3 mm
Shock	Mechanical durability	Min.500 mß
	Malfunction resistance	Min.100 mß
Life	Mechanical	More than 1 million operations
	Electrical	More than 100 thousand operations
Ambient temperature & humidity	-25 ~ 40 °C, 45 ~ 85 % RH	
Storage temperature	-40 ~ 60°C	