



**LOCK WASHER – SHAPE „M“ – BN208010**  
(Version „middle“ for high-strength fastening and normal bearing surfaces)

For screws with metric thread	d1 (mm)	d2 (mm)	h (mm)	s (mm)	kg / 1000
M 4	4,10 - 4,48	9,80 - 10,20	1,25 - 1,50	0,95 - 1,05	0,470
M 5	5,10 - 5,48	11,80 - 12,20	1,55 - 1,90	1,16 - 1,24	0,790
M 6	6,10 - 6,48	13,77 - 14,20	1,85 - 2,20	1,36 - 1,44	1,240
M 8	8,20 - 8,78	17,68 - 18,20	1,95 - 2,40	1,36 - 1,44	2,030
M 10	10,20 - 10,78	21,73 - 22,25	2,25 - 2,75	1,55 - 1,65	3,490
M 12	12,40 - 12,83	26,73 - 27,25	2,60 - 3,10	1,75 - 1,85	6,010
M 14	14,40 - 14,83	29,63 - 30,25	3,20 - 3,70	2,34 - 2,46	9,370
M 16	16,40 - 16,98	31,88 - 32,50	3,45 - 3,95	2,44 - 2,56	10,65
M 18	18,50 - 19,25	34,38 - 35,00	4,00 - 4,50	2,94 - 3,06	15,20
M 20	21,00 - 21,75	39,38 - 40,00	4,20 - 4,70	2,94 - 3,06	20,40
M 22	23,00 - 23,75	44,38 - 45,00	4,80 - 5,30	3,44 - 3,56	30,40
M 24	25,00 - 25,75	49,38 - 50,00	5,10 - 5,60	3,44 - 3,56	38,20
M 27	28,00 - 28,85	59,26 - 60,00	6,10 - 6,60	3,91 - 4,09	69,00
M 30	31,00 - 31,85	69,26 - 70,00	7,30 - 7,80	4,41 - 4,59	109,00

Available material versions: stainless steel A4 or Spring steel hardened 420 – 510 HV 10 with zinc flake coating